

# SAFETY DATA SHEET

## GARDX STAGE 2

### 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

**PRODUCT NAME** GARDX STAGE 2  
**PRODUCT NO.** ATTS02  
**SUPPLIER** GARDX PROTECTION LTD  
UNIT 1 LOCKYER COURT  
INMANS LANE  
PETERSFIELD  
HANTS  
GU32 2NA  
01730 710220

### 2 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
WHITE SPIRIT	265-185-4	64742-82-1	10-30%	Xn;R65. N;R51/53. R10,R66.
REGULAR KEROSENE		8008-20-6	1-5%	Xn;R65. Xi;R38. N;R51/53. R10.
FLUOROPOLYMER DISPERSION			1-5%	R52.

The Full Text for all R-Phrases are Displayed in Section 16

### 3 HAZARDS IDENTIFICATION

Flammable. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Repeated exposure may cause skin dryness or cracking.

**CLASSIFICATION** N;R51/53. R10, R66.

### 4 FIRST-AID MEASURES

#### INHALATION

Move the exposed person to fresh air at once. Keep the affected person warm and at rest. Get prompt medical attention.

#### INGESTION

Rinse mouth thoroughly. DO NOT induce vomiting. Get medical attention immediately.

#### SKIN CONTACT

Rinse the skin immediately with lots of water.

#### EYE CONTACT

Rinse the eye with water immediately. Continue to rinse for at least 15 minutes and get medical attention.

### 5 FIRE-FIGHTING MEASURES

#### EXTINGUISHING MEDIA

Fire can be extinguished using: Foam, carbon dioxide or dry powder.

### 6 ACCIDENTAL RELEASE MEASURES

#### SPILL CLEAN UP METHODS

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Absorb with inert, damp, non-combustible material, then flush area with water.

### 7 HANDLING AND STORAGE

#### USAGE PRECAUTIONS

Keep away from heat, sparks and open flame.

#### STORAGE PRECAUTIONS

Store at moderate temperatures in dry, well ventilated area. Keep away from heat, sparks and open flame.

### 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

# GARDX STAGE 2

Name	Std	LT - ppm	LT - mg/m3	ST - ppm	ST - mg/m3
WHITE SPIRIT	WEL		600 mg/m3		
REGULAR KEROSENE	WEL		800 mg/m3		

## PROTECTIVE EQUIPMENT



## HAND PROTECTION

Chemical resistant gloves required for prolonged or repeated contact. Use protective gloves made of: Rubber, neoprene or PVC.

## EYE PROTECTION

Wear approved chemical safety goggles where eye exposure is reasonably probable.

## 9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Liquid
COLOUR	White
ODOUR	Pleasant, agreeable.
RELATIVE DENSITY	0.983 @ 20 °c

## 10 STABILITY AND REACTIVITY

### STABILITY

Stable under normal temperature conditions.

### CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition.

## 11 TOXICOLOGICAL INFORMATION

### MEDICAL SYMPTOMS

EYES AND MUCOUS MEMBRANES. Irritation of eyes and mucous membranes. RESPIRATORY SYSTEM. Upper respiratory irritation. SKIN. Skin irritation. DIGESTIVE SYSTEM. Gastrointestinal symptoms, including upset stomach.

## 12 ECOLOGICAL INFORMATION

### ECOTOXICITY

Dangerous for the environment if discharged into watercourses.

## 13 DISPOSAL CONSIDERATIONS

### DISPOSAL METHODS

Dispose of in accordance with local authority requirements.

## 14 TRANSPORT INFORMATION



UN NO. ROAD	1993	ADR CLASS	Class 3: Flammable liquids.
ADR PACK GROUP	3	UN NO. SEA	1993
IMDG CLASS	3	IMDG PACK GR.	3

## 15 REGULATORY INFORMATION

### LABELLING

# GARDX STAGE 2



Dangerous for the environment

## RISK PHRASES

R10 Flammable.  
R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
R66 Repeated exposure may cause skin dryness or cracking.

## SAFETY PHRASES

S2 Keep out of the reach of children  
S35 This material and its container must be disposed of in a safe way.  
S37 Wear suitable gloves.  
S51 Use only in well-ventilated areas.  
S61 Avoid release to the environment. Refer to special instructions/safety data sheets.

## DETERGENT LABELLING

< 5% Non-ionic surfactants  
Perfumes

## 16 OTHER INFORMATION

DATE 24/11/05

### RISK PHRASES IN FULL

R10 Flammable.  
R38 Irritating to skin.  
R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
R52 Harmful to aquatic organisms.  
R65 Harmful: may cause lung damage if swallowed.  
R66 Repeated exposure may cause skin dryness or cracking.

### DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.