

SAFETY DATA SHEET

ENGINE FLUSH - GARDX

Page: 1

Compilation date: 07/07/2015

Revision date: 10/12/2015

Revision No:1.1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: ENGINE FLUSH - GARDX

Product code: T1312

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: GardX International Ltd
Unit 7, Clovelly Business Park, Clovelly Road
Southbourne, Emsworth
Hampshire
PO10 8PE
United Kingdom

Tel: 01243 376 426

Fax: 01243 370 909

Email: info@gardx.co.uk

1.4. Emergency telephone number

Emergency tel: 01405 768 815
(office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Asp. Tox. 1: H304; -: EUH066

Most important adverse effects: May be fatal if swallowed and enters airways. Repeated exposure may cause skin dryness or cracking.

2.2. Label elements

Label elements:

Hazard statements: H304: May be fatal if swallowed and enters airways.

EUH066: Repeated exposure may cause skin dryness or cracking.

Hazard pictograms: GHS08: Health hazard



Signal words: Danger

Precautionary statements: P280: Wear protective gloves.

P301+310: IF SWALLOWED: Immediately call a POISON CENTER/doctor/.

[cont...]

SAFETY DATA SHEET

ENGINE FLUSH - GARDX

Page: 2

P331: Do NOT induce vomiting.

P405: Store locked up.

P501: Dispose of contents/container to to authorised waste disposal site.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

HYDROCARBONS, C11-14, N-ALKANES, ISOALKANES, CYCLIC, <2% AROMATICS - REACH registered number(s): 01-2119456620-43

EINECS	CAS	PBT / WEL	CLP Classification	Percent
926-141-6	-	-	Asp. Tox. 1: H304; -: EUH066	50-70%

HYDROCARBONS, C9, AROMATICS

918-668-5	64742-95-6	-	Flam. Liq. 3: H226; Asp. Tox. 1: H304; STOT SE 3: H335; Aquatic Chronic 2: H411; STOT SE 3: H336	<1%
-----------	------------	---	--	-----

1,2,4-TRIMETHYLBENZENE

202-436-9	95-63-6	-	Flam. Liq. 3: H226; Acute Tox. 4: H332; Eye Irrit. 2: H319; STOT SE 3: H335; Skin Irrit. 2: H315; Aquatic Chronic 2: H411	<1%
-----------	---------	---	---	-----

MESITYLENE

203-604-4	108-67-8	-	Flam. Liq. 3: H226; STOT SE 3: H335; Aquatic Chronic 2: H411	<1%
-----------	----------	---	--	-----

PROPYL BENZENE

203-132-9	103-65-1	-	Flam. Liq. 3: H226; Asp. Tox. 1: H304; STOT SE 3: H335; Aquatic Chronic 2: H411	<1%
-----------	----------	---	---	-----

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water. Remove all contaminated clothes and footwear immediately unless stuck to skin.

Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: Do not induce vomiting. Wash out mouth with water. Consult a doctor.

Inhalation: Move to fresh air in case of accidental inhalation of vapours.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: Nausea and stomach pain may occur. There may be vomiting and diarrhoea.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

[cont...]

SAFETY DATA SHEET

ENGINE FLUSH - GARDX

Page: 3

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Do not induce vomiting. Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Use water spray to cool containers. Suitable extinguishing media for the surrounding fire should be used.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Section 8: Exposure controls/personal protection

8.1. Control parameters

[cont...]

SAFETY DATA SHEET

ENGINE FLUSH - GARDX

Page: 4

Hazardous ingredients:

HYDROCARBONS, C11-14, N-ALKANES, ISOALKANES, CYCLIC, <2% AROMATICS

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1200mg/m ³	-	-	-

1,2,4-TRIMETHYLBENZENE

UK	125 mg/m ³	-	-	-
----	-----------------------	---	---	---

MESITYLENE

UK	25 ppm	-	-	-
----	--------	---	---	---

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Respiratory protection not required.

Hand protection: Gloves (solvent-resistant). Breakthrough time of the glove material > 4 hours.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Environmental: Prevent from entering in public sewers or the immediate environment.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Pale yellow

Odour: Characteristic odour

Evaporation rate: Slow

Oxidising: Not applicable.

Solubility in water: Insoluble

Also soluble in: Most organic solvents.

Viscosity: Non-viscous

Kinematic viscosity: <7.0

Viscosity test method: Kinematic viscosity in 10⁻⁶ m²/s at 40°C (ISO 3104/3105)

Boiling point/range°C: 170-300

Melting point/range°C: No data available.

Flammability limits %: lower: No data available.

upper: No data available.

Flash point°C: >65

Part.coeff. n-octanol/water: No data available.

Autoflammability°C: No data available.

Vapour pressure: No data available.

Relative density: 0.830

pH: Not applicable.

VOC g/l: No data available.

9.2. Other information

Other information: No data available.

[cont...]

SAFETY DATA SHEET

ENGINE FLUSH - GARDX

Page: 5

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions. Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Flames.

10.5. Incompatible materials

Materials to avoid: Oxidising agents. Reducing agents.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

HYDROCARBONS, C11-14, N-ALKANES, ISOALKANES, CYCLIC, <2% AROMATICS

DERMAL	RBT	LD50	>5000	mg/kg
ORAL	RAT	LD50	>5000	mg/kg
VAPOURS	RAT	4H LC50	>5000	mg/kg

HYDROCARBONS, C9, AROMATICS

DERMAL	RBT	LD50	3160	mg/l
ORAL	RAT	LD50	3492	mg/kg
VAPOURS	RAT	4H LC50	6193	mg/l

1,2,4-TRIMETHYLBENZENE

IPR	RAT	LDLO	1752	mg/kg
ORL	RAT	LD50	5	gm/kg

MESITYLENE

IPR	GPG	LDLO	1303	mg/kg
-----	-----	------	------	-------

[cont...]

SAFETY DATA SHEET

ENGINE FLUSH - GARDX

Page: 6

PROPYL BENZENE

ORL	RAT	LD50	6040	mg/kg
-----	-----	------	------	-------

Relevant hazards for substance:

Hazard	Route	Basis
Aspiration hazard	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: Nausea and stomach pain may occur. There may be vomiting and diarrhoea.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

HYDROCARBONS, C11-14, N-ALKANES, ISOALKANES, CYCLIC, <2% AROMATICS

ALGAE	72H IC50	20	mg/l
Daphnia magna	48H EC50	>250	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H LC50	>1000	mg/l

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: Bioaccumulation potential.

12.4. Mobility in soil

Mobility: Insoluble in water. Floats on water. Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

[cont...]

SAFETY DATA SHEET

ENGINE FLUSH - GARDX

Page: 7

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH066: Repeated exposure may cause skin dryness or cracking.

H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H335: May cause respiratory irritation.

H336: May cause drowsiness or dizziness.

H411: Toxic to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.