

SAFETY DATA SHEET

LEATHER GUARD

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name LEATHER GUARD
Product number A0720
Internal identification A0720

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Polish.

1.3. Details of the supplier of the safety data sheet

Supplier GARDX PROTECTION LTD
UNIT 7 CLOVELLY BUSINESS PARK
CLOVELLY ROAD
SOUTHBOURNE, EMSWORTH
HANTS
PO10 8PE
+44 (0)1243 376426

product@gardx.co.uk

1.4. Emergency telephone number

Emergency telephone +44 (0) 777 8505 330 (24 hrs)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards Aerosol 1 - H222, H229
Health hazards Not Classified
Environmental hazards Aquatic Chronic 3 - H412

Classification (67/548/EEC or 1999/45/EC) F+;R12. R52/53,R66.

2.2. Label elements

Pictogram



Signal word Danger

Hazard statements H222 Extremely flammable aerosol.
H229 Pressurised container: may burst if heated
H412 Harmful to aquatic life with long lasting effects.

LEATHER GUARD

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

P501 Dispose of contents/container in accordance with local regulations.

Supplemental label information

EUH066 Repeated exposure may cause skin dryness or cracking.

Detergent labelling

aliphatic hydrocarbons,aliphatic hydrocarbons,aliphatic hydrocarbons,< 5% perfumes,< 5% anionic surfactants,Contains preservation agents,Contains preservation agents,Contains preservation agents,Contains preservation agents,Contains preservation agents,Contains preservation agents

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

HYDROCARBON PROPELLANT	10-30%
CAS number: 68476-85-7	EC number: 270-704-2
Classification	Classification (67/548/EEC or 1999/45/EC)
Flam. Gas 1 - H220	F+;R12.
Press. Gas, Liquefied - H280	
Hydrocarbons, C9-C12, n-alkanes,cyclics,aromatics (2-25%)	10-30%
CAS number: —	EC number: 919-446-0
	REACH registration number: 01-2119458049-33-0000
Classification	Classification (67/548/EEC or 1999/45/EC)
Flam. Liq. 3 - H226	Xn;R65. N;R51/53. R10,R66,R67.
STOT SE 3 - H336	
Asp. Tox. 1 - H304	
STOT SE 3 - H336	
Aquatic Chronic 2 - H411	
Hydrocarbons, C11-14, n-alkanes,cyclic, <2% aromatics	5-10%
CAS number: —	EC number: 926-141-6
	REACH registration number: 01-2119456620-43-xxxx
Classification	Classification (67/548/EEC or 1999/45/EC)
Asp. Tox. 1 - H304	Xn;R65. R66.

LEATHER GUARD

SODIUM NITRITE			<1%
CAS number: 7632-00-0	EC number: 231-555-9	REACH registration number: 01-2119471836-27-xxxx	
M factor (Acute) = 1			
Classification		Classification (67/548/EEC or 1999/45/EC)	
Ox. Sol. 3 - H272		O;R8 T;R25 N;R50	
Acute Tox. 3 - H301			
Eye Irrit. 2 - H319			
Aquatic Acute 1 - H400			

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	If spray/mist has been inhaled, proceed as follows. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.
Ingestion	Rinse mouth thoroughly with water. Get medical attention.
Skin contact	Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.
Eye contact	Rinse immediately with plenty of water. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	Upper respiratory irritation.
Ingestion	Gastrointestinal symptoms, including upset stomach.
Skin contact	Repeated exposure may cause skin dryness or cracking.
Eye contact	May cause temporary eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.
-----------------------------	------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with foam, carbon dioxide or dry powder.
-------------------------------------	---

5.2. Special hazards arising from the substance or mixture

Specific hazards	Extremely flammable aerosol. Pressurised container: may burst if heated
Hazardous combustion products	Thermal decomposition or combustion products may include the following substances: Carbon dioxide (CO ₂). Carbon monoxide (CO).

5.3. Advice for firefighters

Protective actions during firefighting	No specific firefighting precautions known.
---	---

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

LEATHER GUARD

Personal precautions

Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Do not touch or walk into spilled material. Avoid contact with skin, eyes and clothing. Take care as floors and other surfaces may become slippery. Avoid contact with contaminated tools and objects. Provide adequate ventilation. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurised contents and propellant. Wash thoroughly after dealing with a spillage.

6.2. Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Eliminate all sources of ignition. Provide adequate ventilation. Wipe up with an absorbent cloth and dispose of waste safely. Absorb spillage with inert, damp, non-combustible material. Absorb small quantities with paper towels and evaporate in a safe place. Once evaporation is complete, place paper in a suitable waste disposal container and seal securely. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage.

6.4. Reference to other sections

Reference to other sections Wear protective clothing as described in Section 8 of this safety data sheet.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Eliminate all sources of ignition. Wear protective gloves, eye and face protection. Provide adequate ventilation. Avoid contact with skin, eyes and clothing. Do not pierce or burn, even after use. Do not expose to temperatures exceeding 50°C/122°F. Keep out of the reach of children. Wash hands thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions

Keep away from heat, sparks and open flame. Do not expose to temperatures exceeding 50°C/122°F. Store at temperatures between 4°C and 40°C.

Storage class

Flammable compressed gas storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

HYDROCARBON PROPELLANT

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1750 mg/m³

Short-term exposure limit (15-minute): WEL 1250 ppm 2180 mg/m³

Hydrocarbons, C9-C12, n-alkanes,cyclics,aromatics (2-25%)

Long-term exposure limit (8-hour TWA): WEL 350 mg/m³

Hydrocarbons, C11-14, n-alkanes,cyclic, <2% aromatics

Long-term exposure limit (8-hour TWA): WEL 1000 mg/m³

WEL = Workplace Exposure Limit

Hydrocarbons, C9-C12, n-alkanes,cyclics,aromatics (2-25%)

LEATHER GUARD

DNEL	Industry - Inhalation; Short term : 570 mg/m ³
	Industry - Inhalation; Long term : 1980 mg/m ³
	Consumer - Inhalation; Short term : 570 mg/m ³
	Consumer - Dermal; Long term : 1040 mg/kg/day
	Consumer - Inhalation; Long term : 710 mg/m ³
	Consumer - Oral; Long term : 1040 mg/kg/day

SODIUM NITRITE (CAS: 7632-00-0)

DNEL	Industry - Inhalation; Short term systemic effects: 2 mg/m ³
	Industry - Inhalation; Long term systemic effects: 2 mg/m ³
PNEC	- Fresh water; .0054 mg/l
	- Sediment (Freshwater); .0195 mg/kg
	- Intermittent release; .0054 mg/l
	- Sediment (Marinewater); .0223 mg/kg
	- Marine water; .00616 mg/l
	- STP; 21 mg/l
	- Soil; .000733 mg/kg

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Tight-fitting safety glasses. Personal protective equipment for eye and face protection should comply with European Standard EN166.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. For exposure up to 4 hours, wear gloves made of the following material: Rubber (natural, latex). Neoprene. Polyvinyl chloride (PVC). To protect hands from chemicals, gloves should comply with European Standard EN374. The selected gloves should have a breakthrough time of at least 4 hours. The breakthrough time for any glove material may be different for different glove manufacturers. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected.

Hygiene measures

Wash hands thoroughly after handling.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Aerosol.
Colour	Cream.
Odour	Pleasant, agreeable.
pH	Not applicable.
Solubility(ies)	Miscible with water.

9.2. Other information

LEATHER GUARD

Other information	Not determined.
Volatile organic compound	This product contains a maximum VOC content of 324 g/litre.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	There are no known reactivity hazards associated with this product.
-------------------	---

10.2. Chemical stability

Stability	Stable at normal ambient temperatures and when used as recommended.
------------------	---

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Not determined.
---	-----------------

10.4. Conditions to avoid

Conditions to avoid	Avoid heat, flames and other sources of ignition.
----------------------------	---

10.5. Incompatible materials

Materials to avoid	No specific material or group of materials is likely to react with the product to produce a hazardous situation.
---------------------------	--

10.6. Hazardous decomposition products

Hazardous decomposition products	Thermal decomposition or combustion products may include the following substances: Carbon monoxide (CO). Carbon dioxide (CO ₂).
---	---

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg)	105,882.35
-------------------------	------------

Inhalation	Upper respiratory irritation.
Ingestion	Gastrointestinal symptoms, including upset stomach.
Skin contact	Repeated exposure may cause skin dryness or cracking.
Eye contact	May cause temporary eye irritation.

SECTION 12: Ecological Information

Ecotoxicity	The product is not expected to be hazardous to the environment.
--------------------	---

12.1. Toxicity

Acute toxicity - fish	Not determined.
------------------------------	-----------------

12.2. Persistence and degradability

Persistence and degradability	The product is expected to be biodegradable.
--------------------------------------	--

12.3. Bioaccumulative potential

Bioaccumulative potential	The product is not bioaccumulating.
----------------------------------	-------------------------------------

12.4. Mobility in soil

Mobility	The product is partly soluble in water and may spread in the aquatic environment.
-----------------	---

LEATHER GUARD

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects Not determined.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1950

UN No. (IMDG) 1950

UN No. (ICAO) 1950

14.2. UN proper shipping name

Proper shipping name (ADR/RID) AEROSOLS

Proper shipping name (IMDG) AEROSOLS

Proper shipping name (ICAO) AEROSOLS

14.3. Transport hazard class(es)

ADR/RID class 2.1

IMDG class 2.1

ICAO class/division 2.1

Transport labels



14.4. Packing group

ADR/RID packing group 5F

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant
No.

14.6. Special precautions for user

Tunnel restriction code (D)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

LEATHER GUARD

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	Control of Substances Hazardous to Health Regulations 2002 (as amended).
EU legislation	Commission Regulation (EU) No 453/2010 of 20 May 2010. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
Guidance	Workplace Exposure Limits EH40.

15.2. Chemical safety assessment

SECTION 16: Other information

Revision comments	NOTE: Lines within the margin indicate significant changes from the previous revision.
Revision date	26/10/2015
Revision	3.0
Supersedes date	23/04/2013
Risk phrases in full	R10 Flammable. R12 Extremely flammable. R25 Toxic if swallowed. R50 Very toxic to aquatic organisms. R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R65 Harmful: may cause lung damage if swallowed. R66 Repeated exposure may cause skin dryness or cracking. R67 Vapours may cause drowsiness and dizziness. R8 Contact with combustible material may cause fire.
Hazard statements in full	H220 Extremely flammable gas. H222 Extremely flammable aerosol. H226 Flammable liquid and vapour. H229 Pressurised container: may burst if heated H272 May intensify fire; oxidiser. H280 Contains gas under pressure; may explode if heated. H301 Toxic if swallowed. H304 May be fatal if swallowed and enters airways. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H400 Very toxic to aquatic life. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.