

SAFETY DATA SHEET

STAGE 2

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name STAGE 2
Product number B5374/09
Internal identification M169

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Polish.

1.3. Details of the supplier of the safety data sheet

Supplier GARDX PROTECTION LTD
UNIT 7 CLOVELLY BUSINESS PARK
CLOVELLY ROAD
SOUTHBOURNE, EMSWORTH
HANTS
PO10 8PE
+44 (0)1243 376426

product@gardx.co.uk

1.4. Emergency telephone number

Emergency telephone +44 (0) 777 8505 330 (24 hrs)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards Flam. Liq. 3 - H226
Health hazards STOT SE 3 - H336
Environmental hazards Aquatic Chronic 2 - H411

Classification (67/548/EEC or 1999/45/EC) N;R51/53. R10,R66.

2.2. Label elements

Pictogram



Signal word

Warning

Hazard statements

H226 Flammable liquid and vapour.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.
EUH208 Contains METHYL-2H or METHYL-4 (3:1) Mixture of EC NO 220-239-6. May produce an allergic reaction.

STAGE 2

Precautionary statements	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P273 Avoid release to the environment. P312 Call a POISON CENTER/doctor if you feel unwell. P391 Collect spillage. P501 Dispose of contents/container in accordance with local regulations.
Supplemental label information	EUH066 Repeated exposure may cause skin dryness or cracking.
Contains	PETROLEUM DISTILLATE

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

PETROLEUM DISTILLATE	10-30%
CAS number: —	EC number: 919-446-0
	REACH registration number: 01-2119458049-33-0000
Classification Flam. Liq. 3 - H226 STOT SE 3 - H336 Asp. Tox. 1 - H304 STOT SE 3 - H336 Aquatic Chronic 2 - H411	Classification (67/548/EEC or 1999/45/EC) Xn;R65. N;R51/53. R10,R66,R67.
TREATED KAOLIN	1-5%
CAS number: 1332-58-7	EC number: 310-127-6
Classification Not Classified	Classification (67/548/EEC or 1999/45/EC) -
ALUMINIUM SILICATE	1-5%
CAS number: 2141-46-7	
Classification Not Classified	Classification (67/548/EEC or 1999/45/EC) -

STAGE 2

3-iodo-2-propynylbutylcarbamate		<1%
CAS number: 55406-53-6 EC number: 259-627-5		
M factor (Acute) = 10		
Classification	Classification (67/548/EEC or 1999/45/EC)	
Acute Tox. 3 - H301	Xi;R41. N;R50. R43.	
Acute Tox. 4 - H312		
Acute Tox. 4 - H332		
Eye Dam. 1 - H318		
Skin Sens. 1 - H317		
STOT SE 3 - H335		
STOT SE 3 - H335		
Aquatic Acute 1 - H400		

METHYL-2H or METHYL-4 (3:1) Mixture of EC NO 220-239-6		<1%
CAS number: 55965-84-9		
M factor (Acute) = 10	M factor (Chronic) = 10	
Classification	Classification (67/548/EEC or 1999/45/EC)	
Acute Tox. 3 - H301	T;R23/24/25 C;R34 R43 N;R50/53	
Acute Tox. 3 - H311		
Acute Tox. 3 - H331		
Skin Corr. 1B - H314		
Eye Dam. 1 - H318		
Skin Sens. 1 - H317		
Aquatic Acute 1 - H400		
Aquatic Chronic 1 - H410		

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	IF INHALED: Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.
Ingestion	Rinse mouth thoroughly with water. Do not induce vomiting. Get medical attention.
Skin contact	Wash skin thoroughly with soap and water. Get medical attention if irritation persists after washing.
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention if irritation persists after washing.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	Vapours may cause drowsiness and dizziness.
Ingestion	Gastrointestinal symptoms, including upset stomach.
Skin contact	Repeated exposure may cause skin dryness or cracking. May cause an allergic skin reaction.
Eye contact	May cause temporary eye irritation.

STAGE 2

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with the following media: Foam, carbon dioxide or dry powder.

5.2. Special hazards arising from the substance or mixture

Specific hazards The product is flammable.

Hazardous combustion products Thermal decomposition or combustion products may include the following substances:
Carbon dioxide (CO₂). Carbon monoxide (CO).

5.3. Advice for firefighters

Protective actions during firefighting No specific firefighting precautions known.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Do not touch or walk into spilled material. Avoid contact with skin, eyes and clothing. Avoid inhalation of vapours. Provide adequate ventilation. Take care as floors and other surfaces may become slippery. Avoid contact with contaminated tools and objects. Wash thoroughly after dealing with a spillage.

6.2. Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Eliminate all sources of ignition. Contain and absorb spillage with sand, earth or other non-combustible material. Absorb spillage with non-combustible, absorbent material. Collect and place in suitable waste disposal containers and seal securely. Containers with collected spillage must be properly labelled with correct contents and hazard symbol. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage.

6.4. Reference to other sections

Reference to other sections Wear protective clothing as described in Section 8 of this safety data sheet.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Provide adequate ventilation. Avoid contact with skin, eyes and clothing. Do not breathe vapours. Do not eat, drink or smoke when using this product. Wash skin thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store at temperatures between 4°C and 40°C. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Storage class Flammable liquid storage.

7.3. Specific end use(s)

STAGE 2

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

PETROLEUM DISTILLATE

Long-term exposure limit (8-hour TWA): WEL 350 mg/m³

TREATED KAOLIN

Long-term exposure limit (8-hour TWA): WEL 2 mg/m³

ALUMINIUM SILICATE

Short-term exposure limit (15-minute): 10 mg/m³ resp.dust

WEL = Workplace Exposure Limit

PETROLEUM DISTILLATE

DNEL

Industry - Inhalation; Short term : 570 mg/m³
 Industry - Inhalation; Long term : 1980 mg/m³
 Consumer - Inhalation; Short term : 570 mg/m³
 Consumer - Dermal; Long term : 1040 mg/kg/day
 Consumer - Inhalation; Long term : 710 mg/m³
 Consumer - Oral; Long term : 1040 mg/kg/day

ALUMINIUM HYDROXIDE (CAS: 21645-51-2)

DNEL

Workers - Inhalation; Long term systemic effects: 10.76 mg/m³
 Workers - Inhalation; Long term local effects: 10.76 mg/m³
 General population - Oral; Long term systemic effects: 4.74 mg/kg/day

8.2. Exposure controls

Protective equipment



Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Tight-fitting safety glasses. Personal protective equipment for eye and face protection should comply with European Standard EN166.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. For exposure up to 4 hours, wear gloves made of the following material: Rubber (natural, latex). Nitrile rubber. Neoprene. Polyvinyl chloride (PVC). To protect hands from chemicals, gloves should comply with European Standard EN374. The selected gloves should have a breakthrough time of at least 4 hours. The breakthrough time for any glove material may be different for different glove manufacturers. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected.

Hygiene measures

Wash hands thoroughly after handling.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

STAGE 2

Appearance	Creamy liquid.
Colour	Light (or pale). Yellow.
Odour	Pleasant, agreeable.
pH	Not applicable.
Relative density	0.955 @ 25°C
Solubility(ies)	Insoluble in water.
Viscosity	25000 cP @ 25°C

9.2. Other information

Other information	Not determined.
--------------------------	-----------------

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	There are no known reactivity hazards associated with this product.
-------------------	---

10.2. Chemical stability

Stability	Stable at normal ambient temperatures and when used as recommended.
------------------	---

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Not determined.
---	-----------------

10.4. Conditions to avoid

Conditions to avoid	Avoid heat, flames and other sources of ignition.
----------------------------	---

10.5. Incompatible materials

Materials to avoid	No specific material or group of materials is likely to react with the product to produce a hazardous situation.
---------------------------	--

10.6. Hazardous decomposition products

Hazardous decomposition products	Thermal decomposition or combustion products may include the following substances: Carbon dioxide (CO ₂). Carbon monoxide (CO).
---	--

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Inhalation	Vapours may cause drowsiness and dizziness.
Ingestion	Gastrointestinal symptoms, including upset stomach.
Skin contact	Repeated exposure may cause skin dryness or cracking.
Eye contact	May cause temporary eye irritation.

Toxicological information on ingredients.

METHYL-2H or METHYL-4 (3:1) Mixture of EC NO 220-239-6

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg)	53.0
--	------

STAGE 2

Species	Rat
Notes (oral LD₅₀)	Estimated value.
ATE oral (mg/kg)	53.0
<u>Acute toxicity - dermal</u>	
ATE dermal (mg/kg)	300.0
<u>Acute toxicity - inhalation</u>	
ATE inhalation (vapours mg/l)	3.0
<u>Skin sensitisation</u>	
Skin sensitisation	Guinea pig maximization test (GPMT) - Guinea pig: Sensitising.

SECTION 12: Ecological Information

Ecotoxicity Toxic to aquatic life with long lasting effects.

12.1. Toxicity

Acute toxicity - fish Not determined.

Ecological information on ingredients.

METHYL-2H or METHYL-4 (3:1) Mixture of EC NO 220-239-6

Acute aquatic toxicity

LE(C)₅₀	0.01 < L(E)C ₅₀ ≤ 0.1
M factor (Acute)	10
Acute toxicity - fish	Estimated value. LC ₅₀ , 96 hours: 13 mg/l, Fish

Chronic aquatic toxicity

NOEC	0.001 < NOEC ≤ 0.01
Degradability	Non-rapidly degradable
M factor (Chronic)	10

12.2. Persistence and degradability

Persistence and degradability The product is expected to be biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential The product is not bioaccumulating.

12.4. Mobility in soil

Mobility The product has poor water-solubility.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects Not determined.

STAGE 2

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID)	1993
UN No. (IMDG)	1993
UN No. (ICAO)	1993
UN No. (ADN)	1993

14.2. UN proper shipping name

Proper shipping name (ADR/RID) FLAMMABLE LIQUID, N.O.S. (petroleum distillate)

Proper shipping name (IMDG) FLAMMABLE LIQUID, N.O.S. (petroleum distillate)

Proper shipping name (ICAO) FLAMMABLE LIQUID, N.O.S. (petroleum distillate)

Proper shipping name (ADN) FLAMMABLE LIQUID, N.O.S. (petroleum distillate)

14.3. Transport hazard class(es)

ADR/RID class	3
IMDG class	3
ICAO class/division	3

Transport labels



14.4. Packing group

ADR/RID packing group	III
IMDG packing group	III
ICAO packing group	III

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

Tunnel restriction code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

STAGE 2

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	Control of Substances Hazardous to Health Regulations 2002 (as amended).
EU legislation	Commission Regulation (EU) No 453/2010 of 20 May 2010. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
Guidance	Workplace Exposure Limits EH40.

15.2. Chemical safety assessment

SECTION 16: Other information

Revision comments	NOTE: Lines within the margin indicate significant changes from the previous revision.
Revision date	26/10/2015
Revision	3.0
Supersedes date	24/08/2015
SDS number	24888
Risk phrases in full	Not classified. R10 Flammable. R22 Harmful if swallowed. R38 Irritating to skin. R41 Risk of serious damage to eyes. R48/22 Harmful: danger of serious damage to health by prolonged exposure if swallowed. R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R65 Harmful: may cause lung damage if swallowed. R66 Repeated exposure may cause skin dryness or cracking. R67 Vapours may cause drowsiness and dizziness.
Hazard statements in full	H226 Flammable liquid and vapour. H301 Toxic if swallowed. H304 May be fatal if swallowed and enters airways. H311 Toxic in contact with skin. H312 Harmful in contact with skin. H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H331 Toxic if inhaled. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. EUH208 Contains METHYL-2H or METHYL-4 (3:1) Mixture of EC NO 220-239-6. May produce an allergic reaction.

STAGE 2

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.